

DIMENSIONAL DATA FOR 2012 ROLEX MOLDS(SEGMENTED)

JAN. 03, 2012

SIZE DESIGNATION	O.D.	CIRC.	UNLOADED RADIUS	LOADED RADIUS	LOAD (lbs)	TREAD WIDTH	SECT. WIDTH	MEAS. RIM	PSI	WGT. (lbs.)	2012 PRICE
GT											
285/645R18 GT-O	25.485	80.063	12.825	12.550	500	10.625	11.562	18X11	30	22.5	\$418
285/645R18 GT-R	25.485	80.063	12.816	12.549	500	10.625	11.562	18X11	30	22.5	\$418
305/650R18 GT-O	25.692	80.700	13.040	12.715	600	11.500	12.500	18X12	30	23.4	\$477
305/650R18 GT-R	25.692	80.700	12.985	12.681	600	11.500	12.500	18X12	30	23.4	\$477
305/660R18 GT-O	26.022	81.750	13.107	12.800	600	11.375	12.250	18X11	30	23.5	\$477
305/660R18 GT-R	26.022	81.750	13.093	12.783	600	11.375	12.250	18X11	30	23.5	\$477
325/680R18 GT-O	26.758	84.063	13.443	13.063	750	12.250	13.000	18x12	30	25.0	\$482
325/680R18 GT-R	26.758	84.063	13.421	13.050	750	12.250	13.000	18x12	30	25.0	\$482
325/710R18 GT-O	27.984	87.900	14.081	13.720	700	12.000	13.700	18X13	30	26.6	\$514
325/710R18 GT-R	27.984	87.900	14.072	13.750	700	12.000	13.700	18X13	30	26.6	\$514
325/710R19 GT-O	27.984	87.900	14.100	13.747	700	12.000	13.700	19X13	30	27.6	\$534
325/710R19 GT-R	27.984	87.900	TBA	TBA	700	12.000	13.700	19X13	30	27.6	\$534
GT WETS											
285/645R18	25.465	80.000	12.732	12.415	500	10.375	11.250	18X11	30	22.5	\$418
305/650R18	25.632	80.515	12.816	12.450	600	11.313	12.250	18X12	30	23.0	\$482
305/660R18	25.883	81.313	12.942	12.613	600	11.250	12.000	18X11	30	23.5	\$477
325/680R18	26.658	83.750	13.329	12.940	750	12.000	12.812	18x12	30	25.6	\$482
325/710R18	28.234	88.688	14.117	13.690	700	11.750	13.313	18X13	30	28.0	\$514
325/710R19	28.234	88.688	14.117	13.690	700	11.750	13.313	19X13	30	28.2	\$534
DP											
320/650R18 DP-O	25.692	80.700	12.846	12.508	600	11.500	12.500	18X12	30	23.3	\$514
325/710R18 DP-O	27.984	87.900	13.992	13.554	700	12.000	13.700	18X13	30	26.8	\$514
DP WETS											
320/650R18	25.632	80.515	12.816	12.450	600	11.313	12.250	18X12	30	23.0	\$514
325/710R18	28.234	88.688	14.117	13.690	700	11.750	13.313	18X13	30	28.0	\$514